

[www.exposurehifi.com](http://www.exposurehifi.com)



(Authorised exposure dealer)

In line with Exposure's policy of continuous improvement, we reserve the right to change technical specifications without prior notice.

**Exposure Electronics Ltd:**

The Works, 59 North Street, Portslade, East Sussex BN41 1DH, England. Tel: +44 1273 423877. Fax: +44 1273 430619

**Exposure Asia Pacific Sdn Bhd:**

The Works Two, 117A, Jalan SS2/24, 47300 Petaling Jaya, Selangor, Malaysia. Tel: +603 7875 8181. Fax: +603 7875 2833

*exposure*  
high fidelity engineering  
since 1974



**SERIES**

Super Power without the Super Price

*exposure*  
high fidelity engineering  
since 1974

## “S” is for Super Power.

Presenting the exciting, all-new, super powerful 2010S series. Packed with much more power to deliver MORE than ever before.

The new, improved 2010 S Integrated Amplifier sees a whopping 50% increase in power, from 50 watts to 75 watts per channel. While the new 2010 S Power Amplifier is punchier than ever before. Add to that the enhanced 2010 S CD Player that boasts a far better mechanism and you have a power hi-fi system that's set to rock your world!

The latest innovation by Exposure, hi-fi specialists since 1974, the new 2010S series is even more powerful than its award-winning predecessor, the original 2010 series, voted ★★★★★ by Hi-Fi Choice (int. amp and power amp) and ★★★★★ by What Hi-Fi (CD Player).

Yet amazingly, it's still priced the SAME as before! Which just goes to show, at Exposure, great hi-fi just gets better and better!

**The new 2010S. Your SUPERPOWER has arrived.**



# 2010 S CD PLAYER

## Enhanced power for more control and lucidity

- Twin Burr-Brown PCM 1704 mono 24 true multi-bit DACs fitted to provide very high resolution.
- CD display can be turned off for improved sound quality.
- Highly optimised audio output circuitry with multiple stages of supply regulation.
- Large toroidal power transformer with separate windings for CD transport mechanism and audio stages. high capacity supply for audio stages.
- Employment of a high-stability crystal clock reference and dedicated, improved power supply regulator for the transport and audio stages to ensure low jitter performance.
- High quality double-sided PCBs for optimum layout and screening.
- Improved contoured all-aluminium casework and extruded front panel control resonance and stray electro-magnetic fields.
- Full-function remote control.
- Three-year guarantee.

### Technical Specifications:

Output level:	2V RMS
Frequency Response:	20Hz – 20KHz $\pm$ 0.03dB
Total Harmonic Distortion:	<0.008%, 20Hz – 20KHz, 0dBFs
Signal to Noise Ratio:	>100dB, A weighted
Digital Outputs:	SP/DIF, Coaxial and “Toslink” Optical
Mains Supply:	110/120V or 220/240V, 50/60Hz (factory set)
Power Consumption:	25 Watts
Dimensions (H x W x D)	90mm x 440mm x 300mm
Gross Weight (packed):	7.0kg
Nett Weight (unpacked)	5.0kg



# 2010 S INTEGRATED AMPLIFIER

# 2010 S POWER AMPLIFIER

# 2010 S CD PLAYER

# 2010 *S* INTEGRATED AMPLIFIER

50% more power for greater detail and dynamics

- High capacity, 200VA custom-made toroidal power transformer and power supply capacitors.
- Improved contoured all-aluminium casework and extruded front panel control resonance and stray electro-magnetic fields.
- High quality capacitors used in-the signal path.
- Uniquely tuned short signal and power supply path PCB.
- Cascade circuitry utilised for improved power supply immunity.
- Sanken bipolar output transistors for dynamic and vivid performance.
- Separate pre-amp output with class A buffer stage.
- Bi-wiring compatible.
- 75 watts per channel into 8 ohms.
- Improved SYSTEM remote control.
- Three-year guarantee.

## Technical Specifications:

Power Output (1KHz): 75 Watts per channel RMS 8 Ohms.

Input Sensitivity: 250mV  
Input Impedance: >14K Ohms, line input  
Pre-amplifier Output: gain +18dB  
Frequency Response: 20Hz – 20 KHz  $\pm 0.5$ dB  
Total Harmonic Distortion: <0.05% at 1 KHz, rated power  
Signal to Noise: >100 dB, A weighted, ref rated output  
Channel Separation: 20Hz – 20KHz, >60dB  
Mains Supply: 110/120V or 220/240V, 50/60Hz (factory set)

Max Power Consumption: 200VA (both channels driven, 8 Ohm load)

Dimensions (H x W x D): 90 mm x 440 mm x 310 mm  
Nett Weight (unpacked): 7 Kg  
Gross Weight (Packed): 9 Kg



# 2010 *S* POWER AMPLIFIER

Increased power for more punch and depth of image

- High capacity, 200VA custom-made toroidal power transformer and power supply capacitors.
- Improved contoured all-aluminium casework and extruded front panel controls resonance and stray electro-magnetic fields.
- High quality capacitors used in-the signal path.
- Very clean and extended low frequency performance.
- Bi-wiring compatible and switchable to mono block mode thereby doubling output current for low impedance loads.
- 75 watts per channel into 8 ohms.
- Three-year guarantee.

## Technical Specifications:

Power Output (Stereo): 75 Watts per channel at 1KHz into 8 Ohms.  
Input Sensitivity: 1V, gain +24dB  
Input Impedance: >18K Ohms  
Frequency Response: 20Hz – 20 KHz  $\pm 0.5$ dB  
Total Harmonic Distortion: <0.02% at 1 KHz, rated power  
Signal to Noise: >110 dB, A weighted, ref rated output  
Channel Separation: >80dB, 20Hz – 20KHz  
Mains Supply: 110/120V or 220/240V, 50/60Hz (factory set)

Power Consumption: 200VA, both channels driven, 8 ohm load

Dimensions (H x W x D): 90 mm x 440 mm x 310 mm  
Nett Weight (unpacked): 7 Kg  
Gross Weight (Packed): 9 Kg

